

Appl. No. 10/047,031
Amendment and/or Reply
to the Office Action of 25 April 2005

Page 2 of 11

1. Amendments to the Claims:

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

1. (Currently Amended) A method of analyzing the correctness of an output signal, the method comprising the steps of:
 - receiving the output signal, the output signal being obtained from signal transformation of an input signal,
 - receiving a first robust feature, the first robust feature being derived from said input signal,
 - deriving a second robust feature from the output signal;
 - determining a reliability of a hash bit;and
 - identifying a degree of similarity between said first robust feature and said second robust feature.
2. (Original) A method as claimed in claim 1, further comprising the step of:
 - correcting the output signal into a corrected signal in dependence on said degree of similarity.
3. (Previously Presented) A method as claimed in claim 1, further comprising the steps of:
 - encoding the input signal into an encoded signal; and
 - transmitting the encoded signal and the first robust feature.
4. (Previously Presented) A method as claimed in claim 1, further comprising the steps of:

Appl. No. 10/047,031
Amendment and/or Reply
to the Office Action of 25 April 2005

Page 3 of 11

receiving an encoded signal;

decoding said encoded signal into an output signal.

5. (Previously Presented) A method as claimed in claim 3, further comprising the step of embedding the first robust feature into the encoded signal through watermark technology.

6. (Currently Amended) A method as claimed in claim 1, ~~characterized in that~~ wherein for each of said input and output signals, a robust feature is derived by:

splitting an information signal in successive time intervals; and

computing a hash value from a scalar property or vector of properties of the information signal within each time interval.

7. (Cancelled).

8. (Currently Amended) A method as claimed in claim ~~[[7]]~~22, wherein the bands are frequency bands having an increasing bandwidth as function of the frequency.

9. (Currently Amended) A method as claimed in claim ~~[[7]]~~22, wherein said property is the energy of a band.

10. (Currently Amended) A method as claimed in claim ~~[[7]]~~22, wherein said property is the tonality of a band.

11. (Currently Amended) A method as claimed in claim 1, ~~characterized in that~~ wherein the transformation is a lossy transformation.

12. (Cancelled).

Appl. No. 10/047,031
Amendment and/or Reply
to the Office Action of 25 April 2005

Page 4 of 11

13. (Currently Amended) A method according to claim ~~[[12]]~~23, wherein the further selected hash value is another hash value of the first block of hash values.

14. (Currently Amended) A method according to claim ~~[[12]]~~23, wherein the further selected hash value is obtained by reversing a bit of the previously selected hash value.

15. (Original) A method according to claim 14, further comprising the steps of receiving information indicative of the reliability of the bits of the selected hash value, and using said information to determine whether to use the selected hash value.

16. (Original) A method according to claim 14, further comprising the steps of receiving information indicative of the reliability of the bits of the selected hash value, and using said information to determine the bit to be reversed.

17. (Currently Amended) A receiver, comprising:

means for receiving an output signal, the output signal being obtained from signal transformation of an input signal,

receiving means for receiving a first robust feature, the first robust feature being derived from the input signal;

analysing means for deriving a second robust feature from the output signal;

a bit reliability determining circuit adapted to determine if a hash bit is reliable; and

comparing means for identifying a degree of similarity between said first robust feature and a second robust feature derived from an input signal so as to obtain a similarity signal.

Appl. No. 10/047,031
Amendment and/or Reply
to the Office Action of 25 April 2005

Page 5 of 11

18. (Original) A receiver according to claim 17, further comprising correcting means for correcting the output signal into a corrected signal in dependence of said similarity signal.

19. (Currently Amended) A receiver according to claim 17, ~~characterized in that~~
wherein the receiver further comprises

receiving means for receiving an encoded signal from a transmitter,
decoding means for transforming the encoded signal into the output
signal.

20. (Original) A transmitter, suitable for transmitting encoded signals to be received by the receiver according to claim 19, comprising:

analyzing means for deriving a first robust feature from an input
signal;

encoder means for encoding the input signal into an encoded
signal; and

transmitting means for transmitting the encoded signal and the first
robust feature.

21. (Cancelled).

22. (New) A method of analyzing the correctness of an output signal, the method comprising the steps of:

receiving the output signal, the output signal being obtained from
signal transformation of an input signal,

receiving a first robust feature, the first robust feature being derived
from said input signal,

deriving a second robust feature from the output signal;

identifying a degree of similarity between said first robust feature
and said second robust feature in each of said time intervals, wherein in each of
a plurality of time intervals a hash value is computed by:

**Appl. No. 10/047,031
Amendment and/or Reply
to the Office Action of 25 April 2005**

Page 6 of 11

transforming the information signal within the time interval into disjoint bands;
calculating a property of the signal in each of said bands;
comparing the properties in the bands with respective thresholds;
and
representing the results of said comparisons by respective bits of the hash value.

23. (New) A method of analyzing the correctness of an output signal, the method comprising the steps of:

receiving the output signal, the output signal being obtained from signal transformation of an input signal,
receiving a first robust feature, the first robust feature being derived from said input signal,
deriving a second robust feature from the output signal; and
identifying a degree of similarity between said first robust feature and said second robust feature; wherein the method further comprises:
a) calculating from the input signal a first block of subsequent hash values corresponding to a first time interval;
b) calculating from the output signal a second block of subsequent hash values corresponding to a second time interval, at least partially overlapping said first interval;
c) selecting one hash value from one of said first and second blocks of hash values;
d) searching for said hash value in the other one of said first and second blocks of hash values;

**Appl. No. 10/047,031
Amendment and/or Reply
to the Office Action of 25 April 2005**

Page 7 of 11

- e) calculating a difference between the first and second blocks of hash values in which the hash value found in step (d) has the same position as the selected hash value in the other one of said first and second blocks;
- f) repeating steps (c)-(e) for a further selected hash value until said difference is lower than a predetermined threshold or until the number of hash values to be selected is lower than a predetermined threshold; and
- g) concluding to a correct operation of said signal transformation if the difference is lower than a predetermined threshold or concluding to a false operation of said signal transformation if the number of hash values to be selected is lower than a predetermined threshold.